

Adjustable shelf height, made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTWZ-16-10-6 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Maximum dimension:	1,000 × 600 mm shelf dimensions
Adjustment dimension:	150 mm
Payload:	200 kg/441 lbs
Castors:	4 swivel castors, 2 with lock, □ 125
Main construction:	Open
Design:	For self-assembly
Weight:	17.8 kg
Width:	1070 mm
Depth:	670 mm
Height:	1652 mm

All information / dimensions are approximate, technical changes reserved. © Hupfer