

Serving trolley in standard version with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. \varnothing 1.0" (25 mm) round tube frame with 3 welded, 31.5 × 19.7" (1000 × 600 mm) deep-drawn shelves with 0.4" (10 mm) high profile edge, lined with sound insulation on the underside, hygienically folded by 1.4" (35 mm) and rebated inwards, designed for easy cleaning. Push bars integrated on both sides into tube frame ensure good manoeuvrability. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, \varnothing 4.9" (125 mm), with pin fastening.

The Hupfer serving trolley SW 10 × 6 / 3 is a welded model delivered ready for use, and has the greatest usable height between the shelves in comparison to other products, while at the same time providing an extensive range of additional options to choose from. The smooth and cavity-free raised edges makes this model easy to clean, and prevents dirt from accumulating in the corners.



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Maximum dimension:	975 × 600 mm shelf dimensions
Capacity:	3 × 1000 × 600
Modular dimension:	278 mm clearance from shelf to shelf
Round tube frame:	\varnothing 25 mm
Number of shelves:	3
Surface load per shelf:	65 kg/m ²
Height of top shelf:	850 mm
Payload:	120 kg/265 lbs
Castors:	4 swivel castors, 2 with lock, \varnothing 125
Main construction:	Open, three-part
Weight:	24.6 kg
Width:	1095 mm
Depth:	695 mm
Height:	950 mm

All information / dimensions are approximate, technical changes reserved. © Hupfer