

Stationary - Kits

Post Kits and Shelf Kits with Camguard™ antimicrobial

5 Post Heights

32", 56", 64", 72", 84"
(81,3 cm, 142,2 cm, 162,6 cm, 182,9 cm, 213,4 cm)

4 Shelf Widths

14", 18", 21", 24"
(35,6 cm, 45,7 cm, 53,3 cm, 61 cm)

8 Shelf Lengths

24", 30", 36", 42", 48", 54", 60", 72"
(61 cm, 76,2 cm, 91,4 cm, 106,7 cm, 121,9 cm, 137,2 cm, 152,4 cm, 182,9 cm)



• Post Kit includes:

Two Posts and one each top and bottom Post Connector.

• Shelf Kit includes:

Two Traverses and Vented or Solid Shelf Plates to complete one shelf.

Features & Benefits

Versatile Storage

For use in any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free.

Fits in Any Space

Units combine together in straight lines by sharing posts of existing units. Corner Connectors, made of reinforced nylon, connect units together in 90° angle. Unique design maximizes valuable space and offers strength and stability. Simplify assembly and reduce costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Two Post Kits required to complete one unit. Molded in dovetails on Posts ensure that Traverses set easily into place.

Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Shelves up to 48" (121,9 cm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 72" (137,2 - 182,9 cm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 24" (61 cm) to 48" (121,9 cm) traverse.

Item No. _____

Specifier Identification No. _____

Code No. _____


Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Post Kit includes two Posts and one set of Post Connectors.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

Easy to Adjust

Requires use of a rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Sturdy reinforced nylon foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and level.

Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses.

Approvals



Components

* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.

Post Kits

code	width in. cm	height in. cm	case lbs. (cube)	case kg. (cube m³)
CSPK1432	14" 35,6	32" 81,3	8.45 (0.32)	3,83 (0,0091)
CSPK1832	18" 45,7	32" 81,3	8.80 (0.32)	3,99 (0,0091)
CSPK2132	21" 53,3	32" 81,3	9.10 (0.32)	4,13 (0,0091)
CSPK2432	24" 61,0	32" 81,3	9.50 (0.32)	4,31 (0,0091)
CSPK1456	14" 35,6	56" 142,2	13.45 (0.41)	6,10 (0,0116)
CSPK1856	18" 45,7	56" 142,2	13.80 (0.41)	6,26 (0,0116)
CSPK2156	21" 53,3	56" 142,2	14.10 (0.41)	6,40 (0,0116)
CSPK2456	24" 61,0	56" 142,2	14.50 (0.41)	6,58 (0,0116)
CSPK1464	14" 35,6	64" 162,6	15.45 (0.46)	7,0 (0,0130)
CSPK1864	18" 45,7	64" 162,6	15.80 (0.46)	7,17 (0,0130)
CSPK2164	21" 53,3	64" 162,6	16.10 (0.46)	7,30 (0,0130)
CSPK2464	24" 61,0	64" 162,6	16.50 (0.46)	7,48 (0,0130)
CSPK1472	14" 35,6	72" 182,9	17.20 (0.52)	7,80 (0,0147)
CSPK1872	18" 45,7	72" 182,9	17.55 (0.52)	7,96 (0,0147)
CSPK2172	21" 53,3	72" 182,9	17.85 (0.52)	8,10 (0,0147)
CSPK2472	24" 61,0	72" 182,9	18.25 (0.52)	8,28 (0,0147)
CSPK1484	14" 35,6	84" 213,4	19.95 (0.61)	9,05 (0,0173)
CSPK1884	18" 45,7	84" 213,4	20.30 (0.61)	9,21 (0,0173)
CSPK2184	21" 53,3	84" 213,4	20.60 (0.61)	9,34 (0,0173)
CSPK2484	24" 61,0	84" 213,4	21.00 (0.61)	9,52 (0,0173)

Corner Connector Set

Case Pack: 1 set

code	description	case lbs. (cube)	case kg. (cube m³)
CSCC	Right and Left	0.76 (0.05)	0,034 (0,0014)

Shelf Kits with Vented Shelf Plates

code	width in. cm	length in. cm	case lbs. (cube)	case kg. (cube m³)
24" (61 cm) Traverses				
CS1424VK	14" 35,6	24" 61,0	7.43 (0.83)	3,37 (0,0235)
CS1824VK	18" 45,7	24" 61,0	7.94 (0.83)	3,60 (0,0235)
CS2124VK	21" 53,3	24" 61,0	8.66 (0.83)	3,93 (0,0235)
CS2424VK	24" 61,0	24" 61,0	8.73 (0.83)	3,96 (0,0235)
30" (76,2 cm) Traverses				
CS1430VK	14" 35,6	30" 76,2	9.16 (0.83)	4,15 (0,0235)
CS1830VK	18" 45,7	30" 76,2	9.69 (0.83)	4,40 (0,0235)
CS2130VK	21" 53,3	30" 76,2	10.67 (0.83)	4,84 (0,0235)
CS2430VK	24" 61,0	30" 76,2	10.92 (0.83)	4,95 (0,0235)
36" (91,4 cm) Traverses				
CS1436VK	14" 35,6	36" 91,4	10.89 (0.83)	4,94 (0,0235)
CS1836VK	18" 45,7	36" 91,4	11.44 (0.83)	5,19 (0,0235)
CS2136VK	21" 53,3	36" 91,4	12.68 (0.83)	5,75 (0,0235)
CS2436VK	24" 61,0	36" 91,4	13.11 (0.83)	5,95 (0,0235)
42" (106,7 cm) Traverses				
CS1442VK	14" 35,6	42" 106,7	12.66 (0.97)	5,74 (0,0274)
CS1842VK	18" 45,7	42" 106,7	13.62 (0.97)	6,18 (0,0274)
CS2142VK	21" 53,3	42" 106,7	15.23 (0.97)	6,91 (0,0274)
CS2442VK	24" 61,0	42" 106,7	15.31 (0.97)	6,94 (0,0274)
48" (121,9 cm) Traverses				
CS1448VK	14" 35,6	48" 121,9	14.35 (1.06)	6,51 (0,0300)
CS1848VK	18" 45,7	48" 121,9	14.94 (1.06)	6,78 (0,0300)
CS2148VK	21" 53,3	48" 121,9	16.69 (1.06)	7,57 (0,0300)
CS2448VK	24" 61,0	48" 121,9	17.50 (1.06)	7,94 (0,0300)
54" (137,2 cm) Traverses				
CS1454VK	14" 35,6	54" 137,2	16.12 (1.24)	7,31 (0,0351)
CS1854VK	18" 45,7	54" 137,2	17.12 (1.24)	7,76 (0,0351)
CS2154VK	21" 53,3	54" 137,2	19.25 (1.24)	8,73 (0,0351)
CS2454VK	24" 61,0	54" 137,2	19.70 (1.24)	8,93 (0,0351)
60" (152,4 cm) Traverses				
CS1460VK	14" 35,6	60" 152,4	17.39 (1.38)	7,89 (0,0390)
CS1860VK	18" 45,7	60" 152,4	18.80 (1.38)	8,53 (0,0390)
CS2160VK	21" 53,3	60" 152,4	21.26 (1.38)	9,64 (0,0390)
CS2460VK	24" 61,0	60" 152,4	21.32 (1.38)	9,67 (0,0390)
72" (182,9 cm) Traverses				
CS1472VK	14" 35,6	72" 182,9	21.10 (1.66)	9,57 (0,0470)
CS1872VK	18" 45,7	72" 182,9	22.55 (1.66)	10,23 (0,0470)
CS2172VK	21" 53,3	72" 182,9	25.53 (1.66)	11,58 (0,0470)
CS2472VK	24" 61,0	72" 182,9	25.96 (1.66)	11,77 (0,0470)

Item No. _____

Specifier Identification No. _____

Code No. _____

Quantity _____

Shelf Kits with Solid Shelf Plates

code	width in. cm	length in. cm	case lbs. (cube)	case kg. (cube m³)
24" (61 cm) Traverses				
CS1424SK	14" 35,6	24" 61,0	7.79 (0.83)	3,53 (0,0235)
CS1824SK	18" 45,7	24" 61,0	8.34 (0.83)	3,78 (0,0235)
CS2124SK	21" 53,3	24" 61,0	9.14 (0.83)	4,14 (0,0235)
CS2424SK	24" 61,0	24" 61,0	9.27 (0.83)	4,20 (0,0235)
30" (76,2 cm) Traverses				
CS1430SK	14" 35,6	30" 76,2	9.62 (0.83)	4,36 (0,0235)
CS1830SK	18" 45,7	30" 76,2	10.20 (0.83)	4,63 (0,0235)
CS2130SK	21" 53,3	30" 76,2	11.28 (0.83)	5,12 (0,0235)
CS2430SK	24" 61,0	30" 76,2	11.61 (0.83)	5,27 (0,0235)
36" (91,4 cm) Traverses				
CS1436SK	14" 35,6	36" 91,4	11.45 (0.83)	5,19 (0,0235)
CS1836SK	18" 45,7	36" 91,4	12.06 (0.83)	5,47 (0,0235)
CS2136SK	21" 53,3	36" 91,4	13.42 (0.83)	6,09 (0,0235)
CS2436SK	24" 61,0	36" 91,4	13.95 (0.83)	6,33 (0,0235)
42" (106,7 cm) Traverses				
CS1442SK	14" 35,6	42" 106,7	13.29 (0.97)	6,03 (0,0274)
CS1842SK	18" 45,7	42" 106,7	14.40 (0.97)	6,53 (0,0274)
CS2142SK	21" 53,3	42" 106,7	16.17 (0.97)	7,33 (0,0274)
CS2442SK	24" 61,0	42" 106,7	16.40 (0.97)	7,44 (0,0274)
48" (121,9 cm) Traverses				
CS1448SK	14" 35,6	48" 121,9	15.11 (1.06)	6,85 (0,0300)
CS1848SK	18" 45,7	48" 121,9	15.78 (1.06)	7,16 (0,0300)
CS2148SK	21" 53,3	48" 121,9	17.71 (1.06)	8,03 (0,0300)
CS2448SK	24" 61,0	48" 121,9	18.63 (1.06)	8,45 (0,0300)
54" (137,2 cm) Traverses				
CS1454SK	14" 35,6	54" 137,2	16.94 (1.24)	7,68 (0,0351)
CS1854SK	18" 45,7	54" 137,2	18.12 (1.24)	8,22 (0,0351)
CS2154SK	21" 53,3	54" 137,2	20.46 (1.24)	9,28 (0,0351)
CS2454SK	24" 61,0	54" 137,2	21.08 (1.24)	9,56 (0,0351)
60" (152,4 cm) Traverses				
CS1460SK	14" 35,6	60" 152,4	18.29 (1.38)	8,30 (0,0390)
CS1860SK	18" 45,7	60" 152,4	19.95 (1.38)	9,05 (0,0390)
CS2160SK	21" 53,3	60" 152,4	22.65 (1.38)	10,27 (0,0390)
CS2460SK	24" 61,0	60" 152,4	22.96 (1.38)	10,41 (0,0390)
72" (182,9 cm) Traverses				
CS1472SK	14" 35,6	72" 182,9	22.20 (1.66)	10,07 (0,0470)
CS1872SK	18" 45,7	72" 182,9	23.91 (1.66)	10,84 (0,0470)
CS2172SK	21" 53,3	72" 182,9	27.19 (1.66)	12,33 (0,0470)
CS2472SK	24" 61,0	72" 182,9	27.89 (1.66)	12,65 (0,0470)

Architect Specs

- Posts:** Internal steel core, reinforced polypropylene exterior.
- Post Connectors:** Reinforced polypropylene.
- Traverses:** Internal steel core, reinforced polypropylene exterior.
- Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard™ antimicrobial.
- Corner Connectors:** Reinforced nylon.
- Adjustable Foot:** Reinforced nylon.
- Seismic Foot:** Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided)
- Wall Fastener:** Stainless steel.

Optional Accessories

- Seismic Foot** (Bolts not provided) CSEQ3 **Color:** Silver **Case pack:** 4 each
- Wall Fastener** CSWF **Color:** Silver **Case pack:** 4 each
- Identification Tag 6"** CSID **Color:** White/Clear **Case pack:** 12 each
- Identification Tag 3"** CSID3 **Color:** White/Clear **Case pack:** 12 each

Standard Color

- Speckled Gray (480)

Approvals



Components

* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.