

Tilting bratt pan, Durapan gas open base. 150 litre capacity.

STANDARD FEATURES

- Anti-splash pouring lip
- Electronic spark ignition
- All controls are serviceable from the front of the unit
- High limit safety device set at 246°C
- Stainless steel clad 16mm cooking surface guaranteed against warping
- Stainless steel coved cornered pans with litre markings
- All stainless steel construction for durability and easy cleaning
- Adjustable, electronic thermostat controls temperature from 37°C to 218°C
- High efficiency heating system with even heat distribution
- Fast heat-up and recovery time—preheats in 11 minutes, full capacity from cold to boiling in 60 minutes
- Spring assist cover with adjustable vent and full width handle
- On/Off switch, thermostat knob and pilots, recessed to avoid breakage
- Four stainless steel, level adjustable feet, rear flanged for bolting
- Two pilot lights; Green = Power on, Amber = Temperature cycling
- Splash proof controls and water tight electrical connections
- Power Tilt with Hand Tilt Override (PT2)

OPTIONAL FEATURES

- Food Strainers for pouring spout (FSSK)
- Vegetable Steamers (VS)
- Poaching Pans (PP)
- Sliding Drain Drawer with Splash Screen (SLD)
- Double or Single Pantry Faucet (DPK14, SPK14), includes Faucet Mounting Bracket
- Tangent draw-off valve 51mm (TDS2K)
- Folding splash guard for drain draw (SGSLDTR)



TECHNICAL DATA

External: 1220W x 940D x 1067H mm

Clearance: 153mm Rear, 115mm Right Side (for Faucet)

Power Supply: 1NAC 240V, 1 Phase, 0.83 amp
(1.6m Cable & Plug included) 10A
Gas Consumption: 115mj (NG), 125mj (Propane)

Gas Connection: 3/4"

Capacities (per kettle):
(in 115 gram servings, other sizes may be calculated)
40 gallons / 150 litres - 1280 servings

AGA Approval no.: AGA SC404G






SHIPPING DATA

Shipping Weight: 283 kg
Shipping Dimensions: 1219W x 1473D x 1372H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

DIMENSIONS

MODEL	A	B	C	G
SGL-40-TR	1220mm	1118mm	308mm	1140mm



NOTE: NON STANDARD ITEMS ARE SHOWN IN GRAY