

Single-body cooker with gas hob in AISI 304 stainless steel. 1.5 mm pressed top, designed for back-to-back alignment and to accommodate the water column accessory.

Appliance comprises 4 sealed burners with maximum output of 6 kW. Safety tap with thermocouple for continuous output control from 1.6 to 6 kW. Main burner ignition by means of permanent, low-energy pilot burner (170 W). Pilot burner and thermocouple are located underneath the main burner body, protected from accidental impact and any spills. Hob features radiused corners for ease of cleaning and pan supports in RAAF enamelled cast-iron (acid, alkali and flame resistant). Fan oven complete with 1 stainless steel rack. Oven equipped with safety thermostat with a range of 110°C to 280°C. Oven dimensions: 570 x 490 x 295h mm. Oven power: 4.2 kW. Appliance equipped with stainless steel height-adjustable feet (850 - 900 mm).

STANDARD FEATURES

- 1.5mm thick pressed stainless steel tops
- Modular design
- Interlocking device supplied with all units
- Flame failure and standing pilot light
- Natural to Propane gas conversion kit
- External gas regulator supplied (specify gas type)

OPTIONAL FEATURES

- Castor kit
- Flexible gas hose with quick disconnect



LEGEND

- G = Gas
- E = Socket

DIMENSIONS

External: 730D x 800W x 870H mm

Oven Dimensions: 570 x 490 x 295H mm

TECHNICAL DATA

Gas Type: Natural or Propane

Total Output (Gas): Natural Gas - 86.4 MJ/h Propane Gas - 86.4 MJ/h

Gas Connection: 1/2"

AGA approval number: AGA7410G

Power Supply: 400V 3NAC 50Hz (Lead & Plug not included)

Total Output (electric): 4.2 kW

SHIPPING DATA

Net Weight: 124kg

Shipping Weight: 138kg

Shipping Dimensions: 840W x 830L x 1100H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

