

Food serving trolley with active, silent cooling

Make

Manufacturer : HUPFER®
Type : SPA/ K – 3 DW
No of article: 0129471

Dimensions

Width : 719 mm
Depth: 1199 mm
Height: 900 mm

Execution

Structure

Food serving trolley made from stainless steel. Seamlessly welded, completely isolated, continuous wells, to receive three containers GN 1/1 – 200 and its subdivisions. Easy recognition of the open respectively shut condition of the drain taps, protected against unintended opening.

Cooling

Cooling by means of coolant R134a, CFC-free, all-around tubing for high cooling capacity, 6 °C air temperature within the well. Operation by means of ON/OFF switch with integrated control lamp, easily visible from a distance. Flexible spiral cable of constant shape with angular socket and additional socket holder. Easy handling due to the well-chosen position of the cable underneath the cooling module.

Ergonomics

Two push handles, ergonomically shaped, at the front side, with integrated bumper edges protecting against injuries to hands and damages to the device. Castors with disc bumpers at the chassis for protection against collision.

Chassis

Lower frame structure, 25 mm x 25 mm, fully welded, for bottom shelf. 2 swivel castors with total clamps and 2 fixed castors for heavy loads. Castors made from corrosion resistant and maintenance-free plastic with precision ball bearing, Ø 125 mm, according to DIN 18867 part 8.



from the world of Comcater!

National Head Office
156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne
96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney
20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane
1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth
16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799

COMCATER
- foodservice equipment

www.comcater.com.au

Technical Data

Number of wells:	1
Size of wells:	for 3 x GN 1/1 – 200 and its subdivisions
Connected load:	0,30 kW
Cooling capacity:	0,22 kW
Electr. connection:	230 V, 1 N AC 50 cyc.
Enclosure:	IPX5
Thermal insulation:	special insulation
Load capacity per castor:	100 kg
Load capacity per trolley:	225 kg
Net weight:	69 kg

from the world of Comcater!

National Head Office

156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne

96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney

20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane

1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth

16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799



www.comcater.com.au