



eVent



Serie BK

Panel thickness	70 mm	50 mm
Blast Chilling cycles	4 (Light-Soft- Medium-Fast)	2 (Soft- Hard)
Shock Freezing cycles	4 (Light-Soft- Hard - Run)	1
Continuous Shock Freezing cycle	✓	✗
Control Panel	ergonomic on the door	on the air inlet
Handle	Stainless steel ergonomic handle	Built-in handle
Panel Interface	Backlit ergonomic display	Membrane
Multi language scrolling display	✓	✗
Display 9 alphanumerical characters	✓	✗
Parameters described with text	✓	✗
Air inlet	extended	limited
"UP" model available on the 5 trays model	✓	✗
Dedicated Gelato function	✓	✗
Thawing cycle	✓	✗
Second core probe option	✓	✗
USB key	cycles and alarms download with time set options	optional without separate file download
Automatic software update through USB key	✓	✗



eVent

Serie BK

Possibility to transfer both parameters and programs between two Blast Chiller	✓	✗
Dynamic Frost Control (DFC patented algorithm)	✓	✗
Possibility to store up to 99 programs with full description	✓	✗
Scrolling probe values during each cycle	✓	✗
Backlit logo, one colour per each status (alarm, cycle, stand-by)	✓	✗
Core probe sensor	PT1000 (more accurate)	PTC
Alarm list HACCP available through the scrolling display	✓	✗
Automatic hot gas defrost cycle	✓	✗
Drying cycle	✓	✗
Defrost water tray	✓	✗
Pressed internal floor	✓	✗
External body rounded and welded	✓	✗
Condenser Filter	✓	✗
Reversible door	✓	✗
Boosted condenser unit	✓	✗
Water cooled	✓	✗
Remote condenser unit (only on some models)	✓	✗